



Receiver for removable cast bollards.  
9020, 9022, 9023, 9024

GRAVEL BASE IS SUGGESTED FOR DRAINAGE. RECEIVER IS OPEN AT THE BOTTOM.

CONCRETE PROFILE AND SUMP DEPTH TO BE DETERMINE BY INSTALLER BASED ON SITE CONDITIONS.

LOCK TAB OPENING MUST BE KEPT CLEAR. PROTECT WITH TAPE DURING CONCRETE POUR.

THE SUPPLIED CAP IS FOR TEMPORARY SHORT TERM COVERAGE AND NOT FOR HIGH SPEED VEHICLE TRAFFIC. AN OPTIONAL LONG TERM CAP MAY BE ORDERED.

IRONSMITH BOLLARD RECEIVER

This drawing embodies a confidential proprietary design of IRONSMITH BOLLARD RECEIVER, Palm Desert, Ca. All design, manufacturing, reproduction, use, sale, and other rights regarding the same are expressly reserved. This drawing is submitted under confidential relationship for a specific purpose and the recipient agrees by accepting this drawing not to supply or disclose any information regarding it to any unauthorized person or to incorporate any special feature peculiar to this design in other projects. The information in this drawing may be covered completely or in part by patents pending.

**IRONSMITH**  
41-701 Corporate Way #3  
Palm Desert, CA 92260  
(800) 338-4766  
(760) 776-5080 Fax